



SMC Nozzle with Male Thread series KN

- Nozzle with male thread
- Pivoting nozzle with male thread
- Max operating pressure: 1.0MPa
- Variety of tube materials available

Characteristics

Series: KN

Type: KNK

Thread type	Connection	Connection	Max. temperature	Weight	Max. operation pressure	Diameter	Length	Article
		in	°	kg	bar	mm	mm	
Taper [R]	1/8	60	0.008	10	1	21.4		KN-R01-100
Taper [R]	1/4	60	0.022	10	6	27.1		KN-R02-600
Taper [R]	1/4	60	0.02	10	1.5	31		KN-R02-150
Taper [R]	1/4	60	0.032	10	4	38		KNK-R02-400
Taper [R]	1/4	60	0.021	10	2	30.5		KN-R02-200
Taper [R]	1/4	60	0.021	10	2.5	30.1		KN-R02-250
Taper [R]	1/4	60	0.019	10	1	31.4		KN-R02-100

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.