



SMC Lubricator series AL10-60-A

- Body sizes available: 10 ~ 60
- Thread type: M5, Rc(PT), NPT, G(PF)
- Port sizes: M5, 1/8, 1/4, 3/8, 1/2, 3/4, 1

Characteristics

Series: AL-A

Housing material: Zinc die-cast

Ambient temperature: -5 / 60 °C

Size	Port thread type	Port Size in	Bowl Material	Flow direction	Maximum operating pressure	Article
20	BSPP [G]	1/8	Polycarbonate	left ? right	10	AL20-F01-A
20	BSPP [G]	1/4	Polycarbonate	left ? right	10	AL20-F02-A
30	BSPP [G]	1/4	Polycarbonate	left ? right	10	AL30-F02-A
30	BSPP [G]	3/8	Polycarbonate	left ? right	10	AL30-F03-A
40	BSPP [G]	1/4	Polycarbonate	left ? right	10	AL40-F02-A
40	BSPP [G]	1/2	Polycarbonate	left ? right	10	AL40-F04-A
40	BSPP [G]	1/2	Polycarbonate	left ? right	10	AL40-F04B-A
40	BSPP [G]	3/4	Polycarbonate	left ? right	10	AL40-F06-A
50	BSPP [G]	1	Polycarbonate	left ? right	10	AL50-F10-A
60	BSPP [G]	1	Metal	left ? right	10	AL60-F10-8-A
60	BSPP [G]	1	Polycarbonate	left ? right	10	AL60-F10-A

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.