



MHA ZENTGRAF 3-Way ball valve Series: BK3 Steel Cutting ring, heavy [S] PN315/500

Characteristics

Series: BK3
Norm: EN [DIN]
Construction type: 3-way
Housing construction: 4-part
Housing material: Steel
Material quality: Forged steel
Surface protection: Zinc Plated
Connection: Cutting ring, heavy [S]
Standard connection: DIN 2353 / ISO 8434-1

Characteristics [2]

Material ball: Steel
Seat material: POM
Spindle material: Steel
Minimum medium temperature [continuous]: -20 °C
Maximum medium temperature [continuous]: 100 °C

Nominal inner diameter	External tube diameter of connection	Connection, gland nut	Pressure rating	Face to Face norm	Manual operation	Ball bore	Secondary spindle seal material	Body seal	Weight	Article
	mm	mm							kg	
DN04	8	M 16x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.4	14288613
DN04	8	M 16x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.4	14288611
DN06	10	M 18x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.46	14288531
DN06	10	M 18x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.46	14288529
DN08	12	M 20x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.46	14288541
DN08	12	M 20x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.46	14288539
DN10	14	M 22x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.6	14288546
DN10	14	M 22x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.6	14288545
DN13	16	M 24x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.7	14288557
DN13	16	M 24x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.7	14288555
DN13	20	M 30x2	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	0.7	14288567
DN13	20	M 30x2	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	0.7	14288565
DN20	25	M 36x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	1.8	14288577
DN20	25	M 36x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	1.8	14288576
DN25	30	M 42x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	2.4	14601669
DN10	14	M 22x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.6	14613064
DN13	16	M 24x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.7	14613072
DN13	16	M 24x1.5	PN500	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	0.7	14613073
DN13	20	M 30x2	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.7	14613076
DN20	25	M 36x2	PN315	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	1.8	14613080
DN20	25	M 36x2	PN315	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	1.8	14613081
DN25	30	M 42x2	PN315	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	2.4	14613090
DN25	30	M 42x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	2.4	14613091
DN04	8	M 16x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.4	14613096

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	External tube diameter of connection mm	Connection, gland nut mm	Pressure rating	Face to Face norm	Manual operation	Ball bore	Secondary spindle seal material	Body seal	Weight kg	Article
DN06	10	M 18x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.46	14613099
DN08	12	M 20x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	0.46	14613105

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.