



LOWARA Submersible pump Series: DIWA roestvaststaal monofase

Characteristics

Series: DIWA
Chopper: No
Frequency: 50Hz
Length connecting cord: 10 m
Connection: External thread (BSPP)
Connection size: 1.1/2" [40]
Material pump casing: Stainless steel
Material quality: 1.4301

Characteristics [2]

Pump casing material: Stainless steel SS 304 (1.4301)
Level of protection (IP value): IPX8
Insulation class acc. to IEC: F
Medium temperature: 0 / 50 °C
Pump diameter: 178 mm

Discharge head	Maximum flow rate	Max. dimension of fixed parts	Max. immersion depth	With float	Type of switch	Supply voltage	Motor power	Nominal current	Pump height	Article
m	l/min	mm	m				kW	A	mm	
10	250	8	7	Yes	Float switch	1 x 230V AC	0.55	3.4	343	13607163
10	250	8	7	Yes	Vertical level switch	1 x 230V AC	0.55	3.4	343	13607165
13.9	300	8	7	No		1 x 230V AC	0.75	5.1	378	13607169
13.9	300	8	7	Yes	Float switch	1 x 230V AC	0.75	5.1	378	13607164
13.9	300	8	7	Yes	Vertical level switch	1 x 230V AC	0.75	5.1	378	13607166
17	350	8	7	No		1 x 230V AC	1.1	6.7	398	13607170
17	350	8	7	Yes	Float switch	1 x 230V AC	1.1	6.7	398	13375313
17	350	8	7	Yes	Vertical level switch	1 x 230V AC	1.1	6.7	398	13607167

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.