



ERIKS Oil Seal type GRST

The ERIKS oil seal type GRST is similar to the ERIKS oil seal type GR, but features an extra dust lip. As a result, you can keep even more dirt and dust from entering your application. This product complies with the DIN 3760-AS standard. This oil seal is suitable for a wide range of applications, so you are likely to encounter it in all kinds of different industries. Furthermore, the type GRST contains a stainless steel 304 spring, which maintains a balanced pressure at the interface between the rotating shaft and the sealing lip. You use the type GRST oil seal when you want to avoid corrosion and seal a thin fluid in a dynamic application exposed to significant contamination. Do you want to order an oil seal without an extra dust lip, for example, because your application is not exposed to much external contamination? Choose the ERIKS oil seal type GR.



Characteristics

Norm design: DIN 3760-AS


Material lip: FKM

Material surface: Rubber

Equivalent Types: vias

Application

- Recommended in: Chemical



Shaft diameter mm	Housing diameter mm	Article
12	24	10012930
15	24	10012934
15	26	10012935
15	28	11338769
15	30	10012936
15	32	10012937
15	35	12659449
16	24	10012939
16	28	10012940
17	28	10012943
18	30	10012948
18	32	10012950
18	35	10012951
20	30	10012955
20	30	12723789
20	35	10012958
20	40	10012959
22	40	12648505
25	35	10012969
25	40	10012971
25	42	10012972
25	47	10012975
25	52	10012976

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Shaft diameter mm	Housing diameter mm	Article
26	37	10012978
28	47	10012983
28	52	10012984
30	42	10012986
30	42	12659448
30	47	10012989
30	52	10013245
30	55	11338770
30	62	10012992
30	72	10012993
32	40	11194892
32	47	10012995
35	47	10012998
35	50	10013000
35	52	10013001
35	62	10013004
36	50	10013006
36	52	10013007
36	62	10013009
38	55	10013261
38	62	10013262
40	52	10013012
40	55	10013016
40	62	10013017
40	62	10013266
40	72	10013270
40	80	10013272
42	55	10013019
42	62	10013021
42	62	10013022
45	60	11370880
45	62	10013027
45	65	10013028
45	65	10013278
45	72	10013029
45	75	11013182
45	75	10013280
45	80	10013281
45	85	10013282
48	62	10013031
48	65	10013284
48	72	10013034
50	62	11338768
50	65	11370881
50	68	10013035
50	72	10013036
50	72	10013037
50	72	10013287
50	72	10013288
50	80	10013038
50	80	10013290
50	80	10013291
50	90	10013292

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Shaft diameter mm	Housing diameter mm	Article
52	72	10013040
55	70	10013041
55	72	11370973
55	72	10013297
55	80	10013300
55	90	10013302
60	75	10013045
60	80	10013046
60	85	10013047
60	95	11013177
65	80	10013049
65	80	10013312
65	85	10013313
65	90	10013314
68	90	10013315
70	90	11001613
70	95	10013319
70	100	10013349
75	90	10013321
75	100	11370974
75	100	10013352
75	100	11269986
80	100	10013354
80	100	10013356
80	105	10013357
80	110	10013358
85	110	10013361
85	110	10013362
85	120	10013363
90	110	10013368
90	110	10013369
95	115	10013370
95	120	10013372
95	125	10013373
100	120	10013420
100	120	10013422
100	130	10013423
105	125	10013425
105	130	10013427
110	130	10013428
110	130	11315009
110	145	11269985
120	140	10013434
120	150	10013437
125	150	10013439
130	160	10013442
140	170	10013447
160	190	11370976
180	210	10013453
185	210	10013454
190	220	12660799
200	230	10013456
240	270	11370977

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Shaft diameter	Housing diameter	Article
mm	mm	
320	350	10013462
		12110711

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.