

ERIKS Oil Seal type MST


Characteristics

Norm design: DIN 3760-BS

Material lip: NBR

Material surface: Metal

Equivalent Types: EEL, 210, 047, (TR)D, 822S, BSL, MP, 3 [78], CRWA1, OSB-DL, BSN#, TB, BS, DFS, R6, BC, B1SL, AEX DL, WBS



Shaft diameter mm	Housing diameter mm	Article
16	30	10008554
18	30	10008555
20	28	11110678
25	32	10008558
25	40	10008559
25	45	10009125
25	47	10008560
25	52	10009126
30	40	10008562
30	42	10008563
30	45	10008564
31.75	44.45	10012456
35	47	10008566
35	52	10007212
40	52	10005710
42	55	10005726
50	80	10009132
50	90	10009133
60	75	10005764
60	77	10009136
60	80	10007291
62	85	11397473
65	85	10009137

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Shaft diameter	Housing diameter	Article
mm	mm	
65	90	10009138
70	95	10009140
75	100	10009714
90	120	10009718
92.08	117.2	11109071
100	130	10009914
110	130	10009915
145	170	10009178
160	185	10009917
165	190	10009918

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.