



ECON® Switchbox Type: 79653 Aluminium Explosion-proof



Characteristics

Type: 79653
Execution: Switchbox
Explosion-proof: Yes
With console: Yes
Console height: 30 mm
Standard actuator connection: NAMUR [VDI/VDE 3845]
Distance of mounting holes: 80x30 mm
Length drive shaft: 17 mm
With mechanical setting indicator: Yes
Material housing: Aluminium
Surface protection: Powder coating
Material shaft: Stainless steel
O-ring material: NBR
Material konsole: Stainless steel 304
Ambient temperature: -20 / 80 °C

Application

- Feedback of the opening and closing position of manually, pneumatic and hydraulic controlled ball valves, butterfly valves and plug valves.
- Industrial and maritime applications.
- Applications in potentially explosive atmospheres.

Technical Information

- For mounting on actuators with VDI/VDE 3845 connection.
- Aluminum housing IP-67.
- Standard including stainless steel mounting bracket [80 mm x 30 mm x 30 mm (l x w x h)], other dimensions on request [available].
- Optical position indicator [open – closed].
- Equipped with mechanical switches, inductive sensors or REED contacts.
- Suitable for ambient temperatures from -20 °C to +60 °C.
- ATEX versions [Exia-Exd].
- Leakage current, if specified, is the power supply required to operate the switch.

Options

- Optical position indicator for three-way valves with L- or T-bore.
- Mounting kit for the use of manually operated [handle or gearbox] ball valves, butterfly valves or plug valves.

A	B	C	D	ISO5211
mm	mm	mm	mm	
118	139	118	17	F05

Temperature
-20 tot +60 °C

Switch model	Type of switch	Switching function	Number of switches	Supply voltage	Off-state current	Ex-class	Electrical connection	Level of protection [IP value]	Solenoid connection	Article
Mechanical V3	Mechanical		2	250 V AC 16A		EEx d IIC T6	2x M20x1,5	IP67	Yes	12940914
NBB2-V3-E2	Inductive 3-wire NO	Normally open [NO]	2	10 - 30 V DC		EEx d IIC T6	2x M20x1,5	IP67	Yes	12940918
NBB2-V3-Z4L	Inductive 2-wire NO	Normally open [NO]	2	3,7 - 30 V DC	Maximum 0,2 mA	EEx d IIC T6	2x M20x1,5	IP67	Yes	13280261
NBB3-V3-Z4	Inductive 2-wire NO	Normally open [NO]	2	5 - 60 V DC		EEx d IIC T6	2x M20x1,5	IP67	Yes	12940917
NJ2-V3-N	Inductive		2			EEx ia IIC T6	2x M20x1,5	IP67	Yes	12940915
Reedcontact	Mechanical		2			EEx d IIC T6	2x M20x1,5	IP67	Yes	12940916

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.