



PK Gate valve Type: 1850PK steel flange

Characteristics

Type: 1850PK

Norm: ASME

Housing material: Steel

Connection: Flange

DN ["]	L [mm]	H open mm	M mm	Weight [kg]
2	178	339	200	16
3	203	441	250	30
4	229	535	300	44
6	267	735	300	71
8	292	927	350	114
10	330	1125	400	169
12	356	1317	450	247
14	381	1515	500	365
16	407	1824	550	513
20	457	2124	710	823
24	508	2502	800	1276

-29/38 °C	100 °C	150 °C	200 °C	250 °C	300 °C	350 °C	375 °C	400 °C	425 °C	450 °C	475 °C	500 °C	538 °C	
[bar]														
	18,6	17,7	15,8	13,8	12,1	10,2	8,4	7,4	6,5	5,5	4,6	3,7	2,4	1,4
ASTM A216 WCB not recommended for prolonged use over 426°														

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

-29/38 ° C	100 °C	150 °C	200 °C	250 °C	300 °C	350 °C	375 °C	400 °C	425 °C	450 °C	475 °C	500 °C	538 °C
[bar]													
Check the data above to ASME B16.34 (latest edition)													

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.