

SKF Wind turbine blade and yaw grease LGGB 2

- LGBB 2 is a lithium complex/synthetic PAO oil based grease specially designed for extreme conditions involving very low speeds, high loads, low temperatures and oscillating conditions. This grease provides proper lubrication whether the turbine is operating or in stand-still mode, installed onshore, offshore, or in cold climate areas. Excellent false brinelling protection
- Excellent performance under high loads
- Excellent performance at low temperature starting torque
- Good pumpability down to low temperatures
- Excellent water resistance
- Excellent corrosion protection
- High thermal and mechanical stability

Typical applications:

• Wind turbine blade and yaw bearing applications

Characteristics

Series: LGBB 2

Application: Lubrication - grease **Temperature range:** -40 / 120 °C

Colour: Yellow

Droping point: > 200 °C **Thickener:** Lithium-complex **Base oil type:** Synthetic (PAO)

Norm: NLGI 2

DIN standard: DIN 51825 KP2G-40 **Worked penetration 0.1mm:** 265-295

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



Page 1/1

PR10936781501408582_EN_19.04.2024