



CONACO Y-filter Type: 1181 Stainless steel Internal thread (BSPP) Class 800

Characteristics

Type: 1181

Norm: ASME

Housing material: Stainless steel

Connection: Internal thread (BSPP)

Face to Face norm: Manufacturer standard

Filter element material: Stainless steel


Material cover gasket: Graphite spiral wounded

Material drain plug: ASTM A182 F316

Minimum medium temperature (continuous): -29 °C

Maximum medium temperature (continuous): 538 °C

Maximum pressure difference at 20 °C: 1 bar



Application

- Gases, steam, water, oil and other process fluids
- Recommended in: Chemical

Technical Information

- Horizontal piping
- Vertical piping with downwards flow
- Max. differential pressure 0.5bar
- Suitable for suction and delivery piping
- With drain plug as standard

Options

- Available with other perforations
- Available with material certificate EN 10204 3.1

Material quality	Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face length	Perforation size	With measuring connections	Cover model	With drain plug	Material cover	Article
				mm	mm					
ASTM A182 F316	1/2" [15]	ISO 228-1	Class 800	90	0.8	No	Screwed	Yes	ASTM A351 CF8M	13383606
ASTM A182 F316	3/4" [20]	ISO 228-1	Class 800	110	0.8	No	Screwed	Yes	ASTM A351 CF8M	13035260
ASTM A182 F316	1" [25]	ISO 228-1	Class 800	130	0.8	No	Screwed	Yes	ASTM A351 CF8M	13383607
ASTM A182 F316	1.1/2" [40]	ISO 228-1	Class 800	160	0.8	No	Screwed	Yes	ASTM A351 CF8M	13383608

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.