



FENNER Wedge belt Ultra PLUS CRE raw edge moulded notch narrow section XPZ

Fenner

®

Ultra PLUS CRE

Medium duty, cogged raw edge belt



Ideal for high ratio applications often required by today's compact drive envelopes. Combining flexibility with structural stability, it offers higher running efficiency than wrapped belts.

Characteristics

Series: Ultra PLUS CRE

Type: XPZ/3VX

Height: 8 mm

Width (top): 10 mm

Material: CR (polychloroprene)

Tensile Cord: Polyester (PES)

Sheathed: No

Shape-toothed model: Yes

Double V-profile model: No

With perforation: 0

With top layer: No

Temperature resistance: -30 / 70 °C

Construction

- Special compounds improve flexibility and strength
- Higher running efficiency than wrapped belts

Approval

- Fully approved by all international standards
 - BS 3790 (British Standard)
 - ISO 4184 (International Standards Organisation)
 - DIN 7753 (German Institute for Standardization)
 - Static conductive in accordance with ISO 1813
 - Conforms to API (American Petroleum Institute) specifications

Technical Information

- Extended temperature range -30° to +70°C.
- PB® (Precision Built) technology, eliminating the need for matching
- Conditionally oil resistant

Reference length (ISO)	Article
mm	
1162	13370465
1180	13370466
1187	13370467
1337	13370477
1437	13370483
2120	13370513

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.