

ECON® Ball valve Type: 7422 Steel Internal thread (BSPP) Class 300/600



Characteristics

Type: 7422

Norm: ASME

Construction type: 2-way

Housing construction: 3-part

Housing material: Steel

Material quality: ASTM A216 WCB

Surface protection: Chemical blackened

Connection: Internal thread (BSPP)

Standard thread connection: ISO 228-1

Face to Face norm: Manufacturer standard

Top flange standard: ISO 5211 Direct Mount

Material ball: ASTM A351 CF8M

Spindle material: ASTM A276 316 Grade S

Primary spindle seal material: RPTFE

Secondary spindle seal material: FPM (FKM)

Tertiary spindle seal material: RPTFE

Body seal: RPTFE

Material connection piece: ASTM A216 WCB

Actuator material: 1.4301

Minimum medium temperature (continuous): -29 °C

Application

- Industrial and maritime applications.
- Liquid and gaseous media.
- Recommended in: Chemical

Technical Information

- Connection according to ISO 228-1 BSPP.
- Floating ball.
- Pressure class: Class 600 up to and including 2 1/2". Class 300 for 3" and 4".
- With direct-mount top flange according to ISO 5211.
- Closed neck design with leak detection opening.
- The chevron seal set used as a spindle seal and the axial seal ensure a longer service life and lower torque.
- Equipped with a robust, lockable lever.
- Average temperature for a tap with standard TF 4103 seats: -29°C/+220°C. Up to a maximum of 280° C for taps with PEEK seats.

Construction

- Three-part housing construction.
- Design certified according to ISO 7121, MSS SP-110 and MSS SP-72.
- Wall thickness according to EN 12516-1 and ASME B16.34.
- Full or reduced bore.
- Design with antistatic equipment between ball and housing.

Approval


- Fugitive emission certified according to the German Technical Instructions on Air Quality Control [TA-Luft], VDI 2440, point 3.3.1.3.
- Fugitive emission certified according to ISO 15848-1, CO1 and CO2.
- Safety integrity level [SIL] 2.

Options

- Design with worm gearbox, pneumatic, electric or hydraulic drives.
- Position feedback for manual and automatic valves.
- Available with different seat materials such as TF 4215, TFM 1600 and PEEK.
- Fire-safe design available.
- Stainless steel extended spindle for insulation.
- With connection for earthing.
- With 30°, 60° or 90° V-shaped ball bore for modulating applications.
- Connections with NPT thread according to ASME B1.20.1, socket weld according to ASME B16.11 or EN 12760, and butt weld according to ASME B16.25 S40 or EN 12627.

Size table:

DN	Full bore	d mm	L mm	H mm	M mm	Weight kg
1/4" [8]	Yes	15	71	83	140	0.9
3/8" [10]	Yes	15	71	83	140	0.9
1/2" [15]	Yes	15	72	83	140	1
3/4" [20]	No	15	72	83	140	1
3/4" [20]	Yes	20	97	88	140	1.5
1" [25]	No	20	97	88	140	1.5
1" [25]	Yes	25	109	97	165	2
1.1/4" [32]	No	25	109	97	165	2
1.1/4" [32]	Yes	31.8	118	103	165	3
1.1/2" [40]	No	31.8	118	103	165	3
1.1/2" [40]	Yes	38	129	130	202	4.5
2" [50]	No	38	129	130	202	4.5
2" [50]	Yes	50	145	139	202	6.5
2.1/2" [65]	No	50	145	139	202	6.5
2.1/2" [65]	Yes	65	185	178	257	12.5
3" [80]	Yes	76	205	188	257	16.5
3" [80]	Yes	76	205	188	257	16
3" [80]	No	65	185	178	257	12.5
4" [100]	No	76	205	188	257	16.5
4" [100]	Yes	100	240	207.5	405	26



Pressure and temperature range								
Seat material + DN full bore	-29	50	100	150	200	250	300	[°C]
TF4103 & TFM1600 1/4" - 1"	102.1	100.2	68	34	0	-	-	[bar]
TF4215 1/4" - 1"	102.1	100.2	93.2	63	32	0	-	[bar]
PEEK 1/4" - 1"	102.1	100.2	93.2	77	48	18	0	[bar]
TF4103 & TFM1600 1.1/4" - 1.1/2"	80	80	55	28	0	-	-	[bar]
TF4215 1.1/4" - 1.1/2"	80	80	80	55	28	0	-	[bar]
PEEK 1.1/4" - 1.1/2"	80	80	80	77	48	18	0	[bar]
TF4103 & TFM1600 2"	76	76	53	27	0	-	-	[bar]
TF4215 2"	76	76	76	51	25	0	-	[bar]
PEEK 2"	76	76	76	76	47	18	0	[bar]
TF4103 & TFM1600 2.1/2"	69	69	48	24	0	-	-	[bar]

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Pressure and temperature range								
Seat material + DN full bore	-29	50	100	150	200	250	300	[°C]
TF4215 2.1/2"	69	69	69	47	24	0	-	[bar]
PEEK 2.1/2"	69	69	69	69	42	16	0	[bar]
TF4103 & TFM1600 3" - 4"	51.1	50.1	34	17	0	-	-	[bar]
TF4215 3" - 4"	51.1	50.1	46.6	45.1	23	0	-	[bar]
PEEK 3" - 4"	51.1	50.1	46.6	45.1	43.8	17	0	[bar]

Nominal inner diameter	Pressure rating	Manual operation	Mounting flange	Mounting flange 2	Bore	With locking device	Seat material	Maximum medium temperature (continuous) °C	Maximum operating pressure bar	Article
1/4" [8]	Class 600	Handle	F03	F04	Full bore	Yes	TF 4215	230	102	14228443
1/4" [8]	Class 600	Handle	F03	F04	Full bore	Yes	TF 4103	220	102	13278830
3/8" [10]	Class 600	Handle	F03	F04	Full bore	Yes	TF 4103	220	102	13278831
3/8" [10]	Class 600	Handle	F03	F04	Full bore	Yes	TF 4215	230	102	14228444
1/2" [15]	Class 600	Handle	F03	F04	Full bore	Yes	TF 4215	230	102	14228445
1/2" [15]	Class 600	Handle	F03	F04	Full bore	Yes	TF 4103	220	102	13278832
3/4" [20]	Class 600	Handle	F03	F04	Reduced bore	Yes	TF 4215	230	102	14228455
3/4" [20]	Class 600	Handle	F03	F04	Reduced bore	Yes	TF 4103	220	102	13278812
3/4" [20]	Class 600	Handle	F03	F04	Full bore	Yes	TF 4103	220	102	13278833
3/4" [20]	Class 600	Handle	F03	F04	Full bore	Yes	TF 4215	230	102	14228446
1" [25]	Class 600	Handle	F03	F04	Reduced bore	Yes	TF 4103	220	102	13278810
1" [25]	Class 600	Handle	F03	F04	Reduced bore	Yes	TF 4215	230	102	14228454
1" [25]	Class 600	Handle	F04	F05	Full bore	Yes	TF 4103	220	102	13278834
1" [25]	Class 600	Handle	F04	F05	Full bore	Yes	TF 4215	230	102	14228447
1.1/4" [32]	Class 600	Handle	F04	F05	Reduced bore	Yes	TF 4215	230	102	14228456
1.1/4" [32]	Class 600	Handle	F04	F05	Reduced bore	Yes	TF 4103	220	102	13278824
1.1/4" [32]	Class 600	Handle	F04	F05	Full bore	Yes	TF 4215	230	80	14228448
1.1/4" [32]	Class 600	Handle	F04	F05	Full bore	Yes	TF 4103	220	80	13278835
1.1/2" [40]	Class 600	Handle	F04	F05	Reduced bore	Yes	TF 4103	220	80	13278825
1.1/2" [40]	Class 600	Handle	F04	F05	Reduced bore	Yes	TF 4215	230	80	14228457
1.1/2" [40]	Class 600	Handle	F07		Full bore	Yes	TF 4103	220	80	13278836
1.1/2" [40]	Class 600	Handle	F07		Full bore	Yes	TF 4215	230	80	14228449
2" [50]	Class 600	Handle	F07		Reduced bore	Yes	TF 4103	220	80	13278826
2" [50]	Class 600	Handle	F07		Reduced bore	Yes	TF 4215	230	80	14228458
2" [50]	Class 600	Handle	F07		Full bore	Yes	TF 4215	230	76	14228450
2" [50]	Class 600	Handle	F07		Full bore	Yes	TF 4103	220	76	13278837
2.1/2" [65]	Class 600	Handle	F07		Reduced bore	Yes	TF 4103	220	76	13278827
2.1/2" [65]	Class 600	Handle	F07		Reduced bore	Yes	TF 4215	230	76	14228459
2.1/2" [65]	Class 600	Handle	F07	F10	Full bore	Yes	TF 4103	220	69	13278838
2.1/2" [65]	Class 600	Handle	F07	F10	Full bore	Yes	TF 4215	230	69	14228451
3" [80]	Class 300	Handle	F07	F10	Full bore	Yes	TF 4215	230	51	14228452
3" [80]	Class 300	Handle	F07	F10	Full bore	Yes	TF 4103	220	51	13278839
3" [80]	Class 600	Handle	F07	F10	Reduced bore	Yes	TF 4103	220	69	13278828
3" [80]	Class 600	Handle	F07	F10	Reduced bore	Yes	TF 4215	230	69	14228460
4" [100]	Class 300	Handle	F07	F10	Reduced bore	Yes	TF 4215	230	51	14228461
4" [100]	Class 300	Handle	F07	F10	Reduced bore	Yes	TF 4103	220	51	13278829
4" [100]	Class 300	T-wrench	F10		Full bore	No	TF 4215	230	51	14228453
4" [100]	Class 300	T-wrench	F10		Full bore	No	TF 4103	220	51	13278840

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.