



ECON® Ball valve Type: 7442 Stainless steel Internal thread (BSPP) Class 300/600



Characteristics

Type: 7442

Norm: ASME

Construction type: 2-way

Housing construction: 3-part

Housing material: Stainless steel

Material quality: ASTM A351 CF8M

Connection: Internal thread (BSPP)

Top flange standard: ISO 5211 Direct Mount

Material ball: ASTM A351 CF8M

Seat material: TF 4103

Spindle material: ASTM A276 316 Grade S

Primary spindle seal material: RPTFE

Secondary spindle seal material: FPM (FKM)

Tertiary spindle seal material: RPTFE

Body seal: RPTFE

Material connection piece: ASTM A351 CF8M

Actuator material: 1.4301

Minimum medium temperature (continuous): -40 °C

Maximum medium temperature (continuous): 220 °C

Construction

- Three-part housing construction.
- Design certified according to ISO 7121, MSS SP-110 and MSS SP-72.
- Wall thickness according to EN 12516-1 and ASME B16.34.
- Full or reduced bore.
- Design with antistatic equipment between ball and housing.

Approval

- Fugitive emission certified according to the German Technical Instructions on Air Quality Control [TA-Luft], VDI 2440, point 3.3.1.3.
- Fugitive emission certified according to ISO 15848-1, CO1 and CO2.
- Safety integrity level [SIL] 2.
- Declaration of conformity according to EC 1935/2004.

Application

- Industrial and maritime applications.
- Liquid and gaseous media.
- Recommended in: Chemical, Food & Beverages

Technical Information


- Connection according to ISO 228-1 BSPP.
- Floating ball.
- Pressure class: Class 600 up to and including 2.1/2". Class 300 for 3" and 4".
- With direct-mount top flange according to ISO 5211.
- Closed neck design with leak detection opening.
- All components intended to come into contact with food comply with EC 1935.
- The chevron seal set used as a spindle seal and the axial seal ensure a longer service life and lower torque.
- Equipped with a robust, lockable lever.
- Average temperature for a tap with standard TF 4103 seats: -40°C/+220°C. Up to a maximum of 280° C for taps with PEEK seats.

Options

- Design with worm gearbox, pneumatic, electric or hydraulic drives.
- Position feedback for manual and automatic valves.
- Available with different seat materials such as TF 4215, TFM 1600 and PEEK.
- Fire-safe design available.
- Stainless steel extended spindle for insulation or for cold applications (up to -50°C).
- With connection for earthing.
- With 30°, 60° or 90° V-shaped ball bore for modulating applications.
- Connections with NPT thread according to ASME B1.20.1, socket weld according to ASME B16.11 or EN 12760, and butt weld according to ASME B16.25 S40 or EN 12627 or ISO 1127 S1 or SMS 3008 [EN 10357 series D] or DIN 11850 series 1 and 2 [EN 10357 series B and A].

Size table:

DN	Full bore	d mm	L mm	H mm	M mm	Weight kg
1/4" [8]	Yes	15	71	83	140	0.9
3/8" [10]	Yes	15	71	83	140	0.9
1/2" [15]	Yes	15	72	83	140	1
3/4" [20]	No	15	72	83	140	1
3/4" [20]	Yes	20	97	88	140	1.5
1" [25]	No	20	97	88	140	1.5
1" [25]	Yes	25	109	97	165	2
1.1/4" [32]	No	25	109	97	165	2
1.1/4" [32]	Yes	31.8	118	103	165	3
1.1/2" [40]	No	31.8	118	103	165	3
1.1/2" [40]	Yes	38	129	130	202	4.5
2" [50]	No	38	129	130	202	4.5
2" [50]	Yes	50	145	139	202	6.5
2.1/2" [65]	No	50	145	139	202	6.5
2.1/2" [65]	Yes	65	185	178	257	12.5
3" [80]	Yes	76	205	188	257	16.5
3" [80]	No	65	185	178	257	12.5
4" [100]	No	76	205	188	257	16.5
4" [100]	Yes	100	240	207.5	405	26



Pressure and temperature range									
Seat material + DN full bore	-40	50	100	150	175	200	250	300	[°C]
TF4103 & TFM1600 1/4" - 1"	99.3	96.2	72	48	25	0	-	-	[bar]
TF4215 1/4" - 1"	99.3	96.2	84.4	65	45	23	0	-	[bar]
PEEK 1/4" - 1"	99.3	96.2	84.4	77	58	37	13	0	[bar]
TF4103 & TFM1600 1.1/4 " - 1.1/2"	80	80	60	40	20	0	-	-	[bar]
TF4215 1.1/4" - 1.1/2"	80	80	80	61	42	21	0	-	[bar]
PEEK 1.1/4" - 1.1/2"	80	80	80	77	57	36	13	0	[bar]
TF4103 & TFM1600 2"	76	76	56	38	20	0	-	-	[bar]
TF4215 2"	76	76	76	58	39	20	0	-	[bar]
PEEK 2"	76	76	76	76	56	35	12	0	[bar]
TF4103 & TFM1600 2.1/2 "	69	69	52	35	18	0	-	-	[bar]
TF4215 2.1/2"	69	69	69	53	37	19	0	-	[bar]

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Seat material + DN full bore	Pressure and temperature range								[°C]
	-40	50	100	150	175	200	250	300	
PEEK 2.1/2"	69	69	69	69	50	31	10	0	[bar]
TF4103 & TFM1600 3" - 4"	49.6	48.1	37	25	12	0	-	-	[bar]
TF4215 3" - 4"	49.6	48.1	42.2	38.5	37	18	0	-	[bar]
PEEK 3" - 4"	49.6	48.1	42.2	38.5	37	35.7	13	0	[bar]

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Mounting flange 2	Bore	With locking device	Maximum operating pressure bar	Article
1/4" [8]	ISO 228-1	Class 600	Manufacturer standard	Handle	F03	F04	Full bore	Yes	99	13278897
3/8" [10]	ISO 228-1	Class 600	Manufacturer standard	Handle	F03	F04	Full bore	Yes	99	13278899
1/2" [15]	ISO 228-1	Class 600	Manufacturer standard	Handle	F03	F04	Full bore	Yes	99	13278896
3/4" [20]	ISO 228-1	Class 600	Manufacturer standard	Handle	F03	F04	Reduced bore	Yes	99	13278909
3/4" [20]	ISO 228-1	Class 600	Manufacturer standard	Handle	F03	F04	Full bore	Yes	99	13278898
1" [25]	ISO 228-1	Class 600	Manufacturer standard	Handle	F03	F04	Reduced bore	Yes	99	13278904
1" [25]	ISO 228-1	Class 600	Manufacturer standard	Handle	F04	F05	Full bore	Yes	99	13278893
1.1/4" [32]	ISO 228-1	Class 600	Manufacturer standard	Handle	F04	F05	Reduced bore	Yes	99	13278911
1.1/4" [32]	ISO 228-1	Class 600	Manufacturer standard	Handle	F04	F05	Full bore	Yes	80	13278901
1.1/2" [40]	ISO 228-1	Class 600	Manufacturer standard	Handle	F04	F05	Reduced bore	Yes	80	13278910
1.1/2" [40]	ISO 228-1	Class 600	Manufacturer standard	Handle	F07		Full bore	Yes	80	13278900
2" [50]	ISO 228-1	Class 600	Manufacturer standard	Handle	F07		Reduced bore	Yes	80	13278905
2" [50]	ISO 228-1	Class 600	Manufacturer standard	Handle	F07		Full bore	Yes	76	13278894
2.1/2" [65]	ISO 228-1	Class 600	Manufacturer standard	Handle	F07		Reduced bore	Yes	76	13278912
2.1/2" [65]	ISO 228-1	Class 600	Manufacturer standard	Handle	F07	F10	Full bore	Yes	69	13278902
3" [80]	ISO 228-1	Class 300	Manufacturer standard	Handle	F07	F10	Full bore	Yes	49	13278895
3" [80]	ISO 228-1	Class 600	Manufacturer standard	Handle	F07	F10	Reduced bore	Yes	69	13278906
4" [100]	ISO 228-1	Class 300	Manufacturer standard	Handle	F07	F10	Reduced bore	Yes	49	13278907
4" [100]	ISO 228-1	Class 300	Manufacturer standard	T-wrench	F10		Full bore	No	49	13278903

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.