

FLEXION Push in fitting nickel plated brass male elbow BSPT (R)



The push-in fittings of the MPL line are completely made of brass and they are suitable for quick connections in different industrial applications; they are robust, compact and guarantee high performances in time. All MPL fittings are electrolytic nickel-plated.

Characteristics

Type: MPL

Material: Brass, Nickel-plated

Operating temperature: -20 / 80 °C

Operating pressure: -0.99 / 20 bar

Application


- Application : General

Construction

- Protection Ring: POM
- Gripping ring: Stainless Steel AISI 301
- Body : Brass UNI EN 12164 CW614N – UNI EN 12165 CW617N Nickel Plated
- Seals: NBR
- Release Ring: Brass UNI EN 12164 CW614N – UNI EN 12165 CW617N Nickel Plated
- Holding Ring: POM

Approval

- Conformity : SILICONE FREE , RoHS , REACH



Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
				14378190
				14378189
MPL6-02-FX	6	External thread BSPT [R]	1/4	14378194
MPL6-01-FX	6	External thread BSPT [R]	1/8	14378193
MPL8-02-FX	8	External thread BSPT [R]	1/4	14378192
MPL8-01-FX	8	External thread BSPT [R]	1/8	14378191
MPL12-03-FX	12	External thread BSPT [R]	3/8	14378277

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.