

FLEXION Push in fitting nickel plated brass-PBT straight male BSPP(G) and metric



Push in fittings made of a materials "MIX", brass and Technopolymer. This line offers a more competitive priced fitting then the whole brass version, without affecting the fitting performance.

Characteristics

Type: EPC

Material: PBT

Operating temperature: -20 / 80 °C

Operating pressure: -0.99 / 20 bar

Application

- Application : General

Construction

- Protection Ring: POM
- Gripping ring: Stainless Steel AISI 301
- Body : Brass UNI EN 12164 CW614N – UNI EN 12165 CW617N Nickel Plated
- Seals: NBR
- Release Ring: POM
- Holding Ring: POM

Approval

- Conformity : SILICONE FREE , RoHS , REACH

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
EPC4-M5-FX	4	External thread [M]	M 5	13960467
EPC4-M6-FX	4	External thread [M]	M 6	14378281
EPC4-G02-FX	4	External thread BSPP [G]	1/4	13960466
EPC4-G01-FX	4	External thread BSPP [G]	1/8	13960465
EPC6-M5-FX	6	External thread [M]	M 5	13960476
EPC6-G02-FX	6	External thread BSPP [G]	1/4	13960474
EPC6-G01-FX	6	External thread BSPP [G]	1/8	13960473
EPC6-G03-FX	6	External thread BSPP [G]	3/8	13960475
EPC8-G04-FX	8	External thread BSPP [G]	1/2	13960484
EPC8-G02-FX	8	External thread BSPP [G]	1/4	13960482
EPC8-G01-FX	8	External thread BSPP [G]	1/8	13960481
EPC8-G03-FX	8	External thread BSPP [G]	3/8	13960483
EPC10-G04-FX	10	External thread BSPP [G]	1/2	13960452
EPC10-G02-FX	10	External thread BSPP [G]	1/4	13960450
EPC10-G01-FX	10	External thread BSPP [G]	1/8	13960449
EPC10-G03-FX	10	External thread BSPP [G]	3/8	13960451
EPC12-G04-FX	12	External thread BSPP [G]	1/2	13960457
EPC12-G02-FX	12	External thread BSPP [G]	1/4	13960455
EPC12-G03-FX	12	External thread BSPP [G]	3/8	13960456

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.