



FLEXION Push in fitting nickel plated brass-PBT elbow male BSPP(G) and metric

Characteristics

Type: EPL
Material: PBT
Operating temperature: -20 / 70 °C
Operating pressure: -0.99 / 18 bar

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
EPL4-M5-FX	4	External thread [M]	M 5	13960552
EPL4-G01-FX	4	External thread BSPP [G]	1/8	13960550
EPL6-M5-FX	6	External thread [M]	M 5	13960560
EPL6-G02-FX	6	External thread BSPP [G]	1/4	13960558
EPL6-G01-FX	6	External thread BSPP [G]	1/8	13960557
EPL8-G02-FX	8	External thread BSPP [G]	1/4	13960567
EPL8-G01-FX	8	External thread BSPP [G]	1/8	13960566
EPL8-G03-FX	8	External thread BSPP [G]	3/8	13960568
EPL10-G02-FX	10	External thread BSPP [G]	1/4	13960535
EPL10-G03-FX	10	External thread BSPP [G]	3/8	13960536
EPL12-G04-FX	12	External thread BSPP [G]	1/2	13960543
EPL12-G03-FX	12	External thread BSPP [G]	3/8	13960542

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.