



AVENTICS 3/2-directional valve Series ST

Characteristics

Series: ST
Operation: Pneumatic
Type of body: Body Ported

Flow Rate (6 bar - delta p = 1 bar)	Port thread type	Port Size	Operating pressure	Maximum operating pressure	Function	Housing material	Article
NI/min		in	bar	bar			
280	BSPP [G]	1/8	-0.95 / 10	10	3/2	Stainless steel	24104543
280	BSPP [G]	1/8	-0.95 / 10	10	3/2	Stainless steel	12103499
280	BSPP [G]	1/8	-0.95 / 10	10	3/2 Normally closed	Stainless steel	24035906
280	BSPP [G]	1/8	-0.95 / 10	10	3/2 Normally closed	Stainless steel	11303070
280	BSPP [G]	1/8	-0.95 / 10	10	3/2 Normally closed	Stainless steel	12570940
280	BSPP [G]	1/8	-0.95 / 10	10	3/2 Normally closed	Stainless steel	24104542

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.