

AVENTICS 3/2-directional valve Series AP



Characteristics

Series: AP

Operation: Mechanical

Type of body: Body Ported

Flow rate at 6 Bar l/min	Flow Rate (6 bar - delta p = 1 bar) NI/min	Port thread type	Port Size in	Port Size mm	Operating pressure bar	Maximum operating pressure bar	Function	Housing material	Seal material	Article
	550	BSPP [G]	1/4		0 / 10	10	3/2 Normally closed	Aluminium	NBR	11303058
	550	BSPP [G]	1/4		0 / 10	10	3/2 Normally closed	Aluminium	NBR	11303059
	550	BSPP [G]	1/4		0 / 10	10	3/2 Normally closed	Aluminium	NBR	24104535
	550	BSPP [G]	1/4		0 / 10	10	3/2 Normally closed	Aluminium	NBR	24104534
190		Metric		M 5	0 / 10	10	3/2 Normally closed	Aluminium	NBR	12243868
190		Metric		M 5	0 / 10	10	3/2 Normally closed	Aluminium	NBR	11303097
190		Metric		M 5	0 / 10	10	3/2 Normally closed	Aluminium	NBR	24104552
190		Metric		M 5	0 / 10	10	3/2 Normally closed	Aluminium	NBR	12243863
250		BSPP [G]	1/8		0 / 10	10	3/2 Normally closed	Aluminium	NBR	24104544
250		BSPP [G]	1/8		0 / 10	10	3/2 Normally closed	Aluminium	NBR	11303079
250		BSPP [G]	1/8		0 / 10	10	3/2 Normally closed	Aluminium	NBR	12398914
250		BSPP [G]	1/8		0 / 10	10	3/2 Normally closed	Aluminium	NBR	11303078

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.