

CAPTOR Calorimetric flow meter type F4120 - 24VDC




Characteristics

Series: 4120.13

Type: 8262

Process connection: External thread (BSPP)

Supply voltage: 24V DC



Measuring range	Measuring unit	Size process connection	Output signal	Material housing	Article
0 / 3	m/s	1/2" [15]	PNP	Stainless steel 304	10070763
0 / 3	m/s	1/2" [15]	PNP	Stainless steel 304	10070765
0 / 3	m/s	1/2" [15]	PNP	Stainless steel 304	10049880
0 / 3	m/s	1/2" [15]	PNP	Stainless steel 304	10070761
0 / 3	m/s	1/2" [15]	PNP	Stainless steel 316Ti	10049881
0 / 3	m/s	1/2" [15]	PNP	Stainless steel 316Ti	10070762
0 / 3	m/s	1/2" [15]	PNP	Stainless steel 316Ti	10070766
0 / 3	m/s	1/2" [15]	PNP	Stainless steel 316Ti	10070764

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.