



GF 3-way coupling in PVC-C Serie: 540 Glued sleeve/ Internal thread (BSPP)

Characteristics

- Series:** 540
- Material:** PVC-C
- Connection:** Glued sleeve
- Connection 2:** Internal thread (BSPP)
- Seal material:** FPM (FKM)
- Material connection 2:** Stainless steel
- Material quality connection 2:** 1.4404
- Minimum medium temperature (continuous):** 0 °C
- Maximum medium temperature (continuous):** 80 °C

Shape	External tube diameter of connection mm	Nominal inner diameter 2	Pressure rating	Article
3-piece coupling	16	3/8"	PN16	12449022
3-piece coupling	16	3/8"	PN16	12448979
3-piece coupling	20	1/2"	PN16	11233590
3-piece coupling	20	1/2"	PN16	12449024
3-piece coupling	25	3/4"	PN16	11233592
3-piece coupling	32	1"	PN16	11233613
3-piece coupling	32	1"	PN16	12449014
3-piece coupling	40	1.1/4"	PN16	12448984
3-piece coupling	40	1.1/4"	PN16	12448986
3-piece coupling	50	1.1/2"	PN16	12186159
3-piece coupling	63	2"	PN16	11626451
3-piece coupling	63	2"	PN16	12449015

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.