



ASAHI Check valve Series: 33 PVC-U Flange PN4/6/10

Characteristics

Series: 33

Construction type: Straight

Housing material: PVC-U

Connection: Flange

Nominal inner diameter	External tube diameter of connection	Pressure rating	Valve shape	Sealing	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Article
	mm				°C	°C	
DN15	20	PN10	Flap	EPDM	0	60	12478758
DN20	25	PN10	Flap	EPDM	0	60	12478759
DN25	32	PN10	Flap	EPDM	0	60	12478760
DN32	40	PN10	Flap	EPDM	0	60	12478761
DN40	50	PN10	Flap	EPDM	0	60	12356116
DN50	63	PN10	Flap	EPDM	0	60	12478762
DN65	75	PN10	Flap	EPDM	0	60	12478763
DN80	90	PN10	Flap	EPDM	0	60	12478764
DN100	110	PN6	Flap	EPDM	0	60	12478765
DN125	140	PN6	Flap	EPDM	0	60	12478766
DN150	160	PN6	Flap	EPDM	0	60	12478767
DN200	225	PN4	Flap	EPDM	0	60	12478768

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.