



SKF General purpose bearing grease LGMT 2

- LGMT 2 is mineral oil based, lithium soap thickened grease with excellent thermal stability within its operating temperature range. This premium quality, general purpose grease is suitable for a wide range of industrial and automotive applications. Excellent oxidation stability
- Good mechanical stability
- Excellent water resistance and rust inhibiting properties

Typical applications:

- Agricultural equipment
- Automotive wheel bearings
- Conveyors
- Small electric motors Industrial fans

Characteristics

Series: LGMT 2

Application: Lubrication - grease

Temperature range: -30 / 120 °C

Colour: Rust brown

Dropping point: > 180 °C

Thickener: Lithium

Base oil type: Mineral oil

Norm: NLGI 2

DIN standard: DIN 51825 K2K-30

Worked penetration 0.1mm: 265-295

Volume l	Content kg	Packaging	Article
	0.035	Pipe	24007311
	0.2	Pipe	23766634
	1	Can	23766636
	5	Can	23766639
	18	Bucket	23766637
	50	Barrel	23766640
	180	Barrel	23766638
0.42		Cartridge	23766635

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.