



FORMAT Milling cutter insert CCMT M UNI type 2968

ISO milling insert 7° positive, Format

Cutting values for P Steel:

Cutting speed VC: 105?160 m/min.

Feed fz: 0.08?0.15 mm/tooth

Cutting depth: 0.5?3.0 ap/mm

Cutting values for M Stainless:

Cutting speed VC: 60?95 m/min.

Feed fz: 0.08?0.11 mm/tooth

Cutting depth: 0.5?2.3 ap/mm

Cutting values for K Cast iron:

Cutting speed VC: 95?150 m/min.

Feed fz: 0.08?0.15 mm/tooth

Cutting depth: 0.5?3.0 ap/mm

Description	Article
Indexable insert 7deg. pos. CCMT 09T304 M UNI	12741096
Indexable insert 7deg. pos. CCMT 120404 M UNI	12741099
Indexable insert 7deg. pos. CCMT 120408 M UNI	12741101
Indexable insert pos. CCMT 060204 M UNI	12741082
Indexable insert pos. CCMT 060208 M UNI	12741094
Indexable insert pos. CCMT 09T308 M UNI	12741097

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.