

GOODALL Coupling Duracrimp GDS-LF loose flange



Characteristics

Series: Duracrimp

Type: GDS

Type of component: Hose tail coupling

Material: Steel

Connection type: Flange

Hose fitting type: Swivel Flange

Connection termination: EN1092 PN40

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 232 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/2"	DN12	18	261	12735997
3/4"	DN19	18	261	12735998
1"	DN25	18	261	12735999
1/2"	DN12	18	261	12736003
3/4"	DN19	18	261	12736004
1"	DN25	18	261	12736005
DN15	DN12	18	261	12735991
DN20	DN19	18	261	12735992
DN25	DN25	18	261	12735993
1/2"	DN12	18	261	12735994
3/4"	DN19	18	261	12735995
1"	DN25	18	261	12735996
1/2"	DN12	18	261	12736000
3/4"	DN19	18	261	12736001
1"	DN25	18	261	12736002
DN15	DN12	18	261	12735970
DN20	DN19	18	261	12735971

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.