



S & S Globe valve free-flow Type 201 stainless steel entry above the valve pneumatic internal thread

Characteristics

Function: Two-way valve
Construction type: Free-flow
Housing material: Stainless steel
Material quality: 1.4408
Process connection: Internal thread (BSPP)
Face to Face norm: Manufacturer standard
Type of disc: Fixed disc
Actuation: Pressure above the valve
Type of actuator: Pneumatic piston
Function actuator: Spring closing
Position indicator: Yes
Stem seal type: Roof cuffs

Primary spindle seal material: PTFE
Material disk sealing: PTFE
Material disc: 1.4571
Spindle material: 1.4571
Material bonnet: 1.4408
Bonnet gasket material: Fiber Gasket
Max. viscosity: 600 mm²/s

Application

- Steam.
- Gases.
- Recommended in: Food & Beverages

Size process connection	Pressure rating	Kv value m ³ /h	Closing pressure bar	Closing pressure range bar	Type coding actuator	Pilot pressure	Actuator material	Medium temperature °C	Ambient temperature °C	Article
1/2" [15]	PN40	3.5	40		R50	4 - 10 bar	Brass chromium-plated	-30 / 200	-15 / 100	10057528
3/4" [20]	PN40	8		8.7 / 40	R50	3-10 bar	Brass chromium-plated	-30 / 200	-15 / 100	10057532
1" [25]	PN40	15		5.2 / 33	R50	3-10 bar	Brass chromium-plated	-30 / 200	-15 / 100	10057531
1" [25]	PN40	16	33		R80	3.5 - 10 bar	Brass chromium-plated	-30 / 170	-15 / 60	12267689
1.1/4" [32]	PN40	21		3 / 19	R50	3-10 bar	Brass chromium-plated	-30 / 170	-15 / 60	10057530
1.1/4" [32]	PN40	24		15.5 / 35	R80	3-10 bar	Brass chromium-plated	-30 / 170	-15 / 60	12267690
1.1/2" [40]	PN40	30		2.4 / 13	R50	3.5 - 10 bar	Brass chromium-plated	-30 / 170	-15 / 60	10057529
1.1/2" [40]	PN40	35		5.1 / 23	R80	2.5 - 10 bar	Brass chromium-plated	-30 / 170	-15 / 60	12267691
2" [50]	PN40	40		2.6 / 8	R50	4.5 - 10 bar	Brass chromium-plated	-30 / 170	-15 / 60	10057527

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.