## DN10/15 - 50

## **GF Ball valve Series: 546 PVDF Flange PN16**

## **Characteristics**

Series: 546

Construction type: 2-way Housing construction: 3-part Housing material: PVDF Connection: Flange

**Primary spindle seal material:** FPM (FKM) **Secondary spindle seal material:** FPM (FKM)

Body seal: FPM (FKM)

Minimum medium temperature (continuous): -20  $^{\circ}\text{C}$  Maximum medium temperature (continuous): 140  $^{\circ}\text{C}$ 

With drain: No

## **Application**

• Recommended in: Chemical

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Manual operation	Bore	With locking device	Material ball	Seat material	Spindle material	Actuator material	Article
DN20	25	PN16	Handle	Full bore		PVDF	PTFE	PVDF	Plastic	11290730
DN32	40	PN16	Handle	Full bore		PVDF	PTFE	PVDF		11290732
DN50	63	PN16	Handle	Full bore		PVDF	PTFE	PVDF	Plastic	11290744

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

**ERIKS** 

PR1448375853687\_EN\_09.05.2024