



FLEXION Blue polyurethane tube

Characteristics

Type: TU-PU
Hose material: Polyurethane
Hardness [shore]: 98

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	Minimum bursting pressure	Maximum operating pressure at 23 °C	Maximum operating pressure at 60 °C	Article
mm	mm	mm	bar	m		mm	bar	bar	bar	
2.5	0.75	4	15	50	Blue	10	46	15	7	14402529
2.5	0.75	4	15	100	Blue	10	46	15	7	14402515
2.5	0.75	4	15	25	Blue	10	46	15	7	14402528
4	1	6	13	25	Blue	20	40	13	6	14402582
4	1	6	13	50	Blue	20	40	13	6	14402583
4	1	6	13	100	Blue	20	40	13	6	14402555
5.5	1.25	8	14	25	Blue	35	41	14	7	14402532
5.5	1.25	8	14	50	Blue	35	41	14	7	14402533
5.5	1.25	8	14	100	Blue	35	41	14	7	14402518
6.5	1.75	10	14	50	Blue	25	42	14	7	14451929
6.5	1.75	10	14	100	Blue	25	42	14	7	14402519
8	2	12	14	25	Blue	35	40	13	6	14454323

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.