

FENWAL Fire detector type 27121 fig. 3802



Characteristics

- Series:** 27121
- Type:** 3802
- Model:** Fire detector
- Connection:** External thread [NPT]
- Size process connection:** 1/2" [15]
- Maximum contact load:** 5 A
- Electrical connection:** Lead wires
- Explosion-proof:** No
- Approvals:** None

Switching point	Insert length	Sensor diameter	Process connection material	Housing material	Sensor material	Switching function	Article
°F	mm	mm					
140	92.9	15.88	Brass	Brass	Stainless steel	Make (normally open)	11073234
140	92.9	15.88	Stainless steel	Stainless steel	Stainless steel	Make (normally open)	11341287
190	92.9	15.88	Stainless steel	Stainless steel	Stainless steel	Make (normally open)	11149228
225	92.9	15.88	Stainless steel	Stainless steel	Stainless steel	Make (normally open)	11075367
275	92.9	15.88	Brass	Brass	Stainless steel	Make (normally open)	11066393
275	92.9	15.88	Stainless steel	Stainless steel	Stainless steel	Make (normally open)	11070164
325	92.9	15.88	Brass	Brass	Stainless steel	Make (normally open)	11034762
325	92.9	15.88	Stainless steel	Stainless steel	Stainless steel	Make (normally open)	10060379
360	92.9	15.88	Brass	Brass	Stainless steel	Make (normally open)	11039441
360	92.9	15.88	Stainless steel	Stainless steel	Stainless steel	Make (normally open)	11378290
450	92.9	15.88	Stainless steel	Stainless steel	Stainless steel	Make (normally open)	11090505
600	92.9	15.88	Brass	Brass	Stainless steel	Make (normally open)	11125207
600	92.9	15.88	Stainless steel	Stainless steel	Stainless steel	Make (normally open)	10060380

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.