



## NORGREN Oil-fog lubricator EXCELON® series L73C

- Excelon design allows in-line or modular installation
- Flow sensor provides a nearly constant oil/air ratio over a wide range of flows
- All round [360°] visibility of sight-feed dome for ease of drip rate setting
- Micro-fog lubricators for best lubrication in general purpose pneumatic applications

### Characteristics

**Series:** Excelon

**Type:** L73

**Housing material:** Aluminium

**Seal material:** Neoprene®

**Drain type:** None

**Operating temperature:** -34 / 50 °C

**Reservoir capacity:** 0.1 l

| Port thread type | Port Size<br>in | Bowl Material | Maximum operating pressure | Article  |
|------------------|-----------------|---------------|----------------------------|----------|
| BSPP [G]         | 1/4             | Polycarbonate | 10                         | 11584110 |
| BSPP [G]         | 3/8             | Polycarbonate | 10                         | 11584113 |
| BSPP [G]         | 3/8             | Polycarbonate | 10                         | 11584112 |
| BSPP [G]         | 1/2             | Polycarbonate | 10                         | 11584114 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.