

GORE® Expanded PTFE sealing tape GORE 1000

For industrial use only.

Not for use in food, drug, cosmetic, or medical device manufacturing, processing, or packaging operations.

Characteristics

Series: GORE

Type: 1000

Material structure: Multidirectional expanded PTFE

Shape: Flat

Maximum temperature: 230 °C

Minimum temperature: -60 °C

Max. pressure: 10 bar

Suitable for medium: Chlorine Water < 5% [7782-50-5], Air [compressed air], Cryogenic, Alkalis, Strong acids (except hydrofluoric), Natural gas, Refrigerants, Grease, Chlorine, gaseous [7782-50-5], Solvents, Weak Acids, Strong Alkalis, Hydrocarbons, Fuels, Biodiesel, Acids, Weak Alkalis, Oil, Strong Acids, Lubricant

Application

- Recommended in: Chemical

Width mm	Thickness mm	Roller length m	Article
40	3	5	12725307
40	6	10	12725290
40	6	5	12725288
40	6	15	12725291
40	9	5	12725298
40	9	15	12725300
40	9	10	12725299
55	3	5	12725308
55	6	15	12725294
55	6	10	12725293
55	6	5	12725292
55	9	10	12725302
55	9	15	12725303
55	9	5	12725301
65	3	5	12725309
65	6	5	12725295
65	6	10	12725296
65	6	15	12725297
65	9	15	12725306
65	9	10	12725305
65	9	5	12725304

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.