

Hose coupling type SHM HYDR with male thread in stainless steel for ferrule assembly



Characteristics

Type of component: Hose tail coupling

Material: AISI 316

Connection type: Threaded coupling

Hose fitting type: Male thread

Connection termination: NPT

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 260 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/2		160	2320	13015676
1/4"	DN06	315	4568	11180851
3/8"	DN10	315	4568	11180852
1/2"	DN12	315	4568	11180853
3/4"	DN19	160	2320	11180855
1"	DN25	160	2320	11180884
3/8"	DN10	315	4568	12357729
1/2"	DN12	315	4568	12688377
3/4"	DN19	160	2320	11364372
1/4"	DN06	315	4568	11481654
3/8"	DN10	315	4.568	13015678
1/2"	DN12	315	4568	11240660
3/4"	DN19	160	2320	12612693
1"	DN25	160	2320	12612798
2"	DN50	100	1450	11205133

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.