

SHM SMS stainless steel 316 coupling



Characteristics

Type of component: Hose tail coupling

Material: Stainless steel (AISI 316)

Connection type: Threaded coupling

Hose fitting type: Male thread

Characteristics [2]

Connection termination: External dairy thread (DIN405)

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 260 °C



Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/2"	DN12	25	362	12718944
3/4"	DN19	25	362	13555890
1"	DN25	25	362	12934677
1.1/4"	DN32	25	362	13555892
1.1/2"	DN38	25	362	12934676
2"	DN50	25	362	12692264
2.1/2"	DN63	25	362	12945258
3"	DN75	25	362	12715835
4"	DN100	25	362	12401213
1"	DN25	25	362	12692260
1.1/4"	DN32	25	362	12692261

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.