



RUST-OLEUM Floor coating

An easy to apply solvent based Alkyd floor coating specially designed for applying on old (>2 years), dry concrete for interior and exterior use.

- Single pack, solvent based floor coating
- For foot traffic, interior and exterior
- For old concrete floors (>2 yrs), metal and wood
- High gloss appearance, great hiding power
- Touch dry after 6 hours (at 20°C)
- 8 m2 per litre (two coats recommended)
- Available in different RAL colours

The coating has a good resistance against abrasion and neutral detergents (no alkaline cleaning agents) and is resistance during short contact periods against lubricating oils, fuel, petrol etc. 7100 Floor Coating is available in two versions, standard and anti-slip NS. 7100 Floor Coating can also be applied on old good adhering coatings. 7100 can be applied onto metal floors which have been correctly prepared and primed with a suitable Rust-Oleum metal primer.



Colour	RAL-number	Volume ml	Packaging	Degree of gloss	Article
Black	9005	5000	Can	High-gloss	11932528
Green	6005	5000	Can	High-gloss	11932512
Grey	7035	750	Can	High-gloss	11932531
Grey	7035	2500	Can	High-gloss	11932532
Grey	7001	5000	Can	High-gloss	11932540
Grey	7035	5000	Can	High-gloss	11932534
Grey	7035	20000	Can	High-gloss	11932533
Red		2500	Can	High-gloss	11932523
Red		5000	Can	High-gloss	11932525
White	9010	5000	Can	High-gloss	11932545
Yellow	1023	5000	Can	High-gloss	11932519

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.