



GOODALL Robust rubber hose Petralflo SD, NBR1 suction & discharge hose for oil 16 bar; according to EN 12115/ EN 1761, Ω/T



Characteristics

Series: Petralflo

Type: SD

Application

- suction and discharge hose for mineral oil products and fuel mixtures with a maximum 50% aromatics content
- suitable for transport of leadfree fuel
- ideal for applications in which static electricity can occur
- the static charge can be safely conducted away through to the conductive tube and cover, the installation must be grounded
- because of its high flexibility, this hose is especially suitable for tank-truck transport

Technical Information

Temperature range

- -30 °C to +90 °C, depending on medium

Burst pressure

- minimum 64 bar
- safety factor 4:1

Construction

Tube

- black NBR1 rubber
- smooth, homogeneous and seamlessly extruded
- electrically conductive $R < 10^6 \Omega$

Reinforcement

- 2 braided synthetic fabrics
- completely embedded galvanized steel spiral, vacuum resistant
- 2 static wires

Cover

- black CR rubber
- smooth, cloth impression
- wear resistant
- ozone and weather resistant
- electrically conductive $R < 10^6 \Omega$

Execution

Branding

- yellow marking with text: "GOODALL PETRALFLO SD - OIL EN 12115/EN 1761 16 BAR - 232 PSI Ω/T"
- imprinted text: "GOODALL PETRALFLO SD - EN 12115:2011/EN 1761:1999 - NBR1 - SD - diam - 16 bar - Ω/T - month/year"

Connections

- all safety clamp couplings in accordance with EN 14420 (threads, flanges, Eritite [Cam & Groove], Guillemin, TW, etc.)

Assembly

- safety clamps, ferrules or re-usable hose fittings

Approval

Approvals/regulations

- EN 12115
- EN 1761

Options

Complete assembly

- ERIKS can assemble the Petralflo SD with your required couplings.

Options

- hydrostatic test report
- excellent laser engraving on marking ferrule

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	%	mm	m	kg/m	
19	6	31	16	64	90	120	40	0.85	12761677
25	6	37	16	64	90	150	40	1.05	12761678
32	6	44	16	64	90	175	40	1.25	12761680
38	6.5	51	16	64	90	225	40	1.5	12761681
50	8	66	16	64	90	275	40	2.4	12761682
63	8	79	16	64	90	300	40	2.95	12761683
75	8	91	16	64	90	350	40	3.4	12761685
100	8	116	16	64	90	450	40	4.85	12761687
125	9.5	144	16	64	90	600	40	6.65	12761688
150	10	170	16	64	90	750	40	7.85	12761689

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.