



MECAFRANCE Ball valve Type: 3361 Stainless steel Pneumatic operated Single acting, spring closing Internal thread (BSPP) PN50 to PN100

Characteristics

Type: 3361

Norm: EN (DIN)

Construction type: 2-way

Housing construction: 3-part

Housing material: Stainless steel

Material quality: 1.4408

Connection: Internal thread (BSPP)

Actuator: Pneumatic operated


Characteristics (2)

Operating principle: Single acting, spring closing

Top flange standard: ISO 5211

Tertiary spindle seal material: RPTFE

Actuator material: Aluminum anodized



Nominal inner diameter	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
1/2" [15]	PN100	Manufacturer standard	SAF05	AMG	Reduced bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054674
3/4" [20]	PN100	Manufacturer standard	SAF05	AMG	Reduced bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054675
1" [25]	PN100	Manufacturer standard	SAF10	AMG	Reduced bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054677
1.1/4" [32]	PN100	Manufacturer standard	SAF15	AMG	Reduced bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054680
1.1/2" [40]	PN63	Manufacturer standard	SAF15	AMG	Reduced bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054679
2" [50]	PN63	Manufacturer standard	SAF20	AMG	Reduced bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054678
3" [80]	PN50	Manufacturer standard	SAF25	AMG	Reduced bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054681

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.