

VDL Blind flange Series: 3.74 PVC-U Grey Norm: EN 1092-1/02 DIN 2501



Characteristics

Series: 3.74

Norm: EN 1092-1/02

Flange type: Blind flange

Flange standard: DIN 2501

Material: PVC-U

Colour: Grey

Application


- Can be used in combination with collar bushing, transfer flange and flat seal

Technical Information

- Connection dimensions in accordance with EN 1092/DIN 2501.
- Flange bore PN10.

Execution

- Mounting method in accordance with DVS 2210-1, addendum 3, and DIN 16962-12.
- Only use undamaged and clean products.
- 1 seal per connection.
- Mount the collar bushings completely parallel.
- Grease the nuts and bolts.
- Observe and mark the prescribed tightening sequence.
- Tighten to the specified torque in five steps: Hand-tight/wrench-tight, 30%, 60%, 100%, full check [clockwise].
- Tighten the connections after pressing out.



Pressure rating flange	Nominal inner diameter	External tube diameter of connection	Pitch circle	Number of bolt holes	Diameter bolt hole	Thickness flange	Article
		mm	mm		mm	mm	
PN10	DN20	25	73	4	16	12	12976148
PN10	DN25	32	83	4	16	14	11236731
PN10	DN32	40	100	4	18	15	12976149
PN10	DN40	50	110	4	18	16	12976121
PN10	DN50	63	124	4	18	18	12976150
PN10	DN65	75	145	4	18	19	11249359
PN10	DN80	90	160	8	18	20	11260950
PN10	DN100	110	180	8	18	22	12976122

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.