



ACS Hydrostatic level transmitter fig 8352 series S50 sanitary connection

Characteristics

Series: S50-FN
Type: 8352
Model: Hydrostatic level transmitter
Measuring method: Pressure
Max. pressure: 6 bar
Relative accuracy of measurement: 0.2 %
Process connection: Tri-clamp ISO 2852
Membrane material: Ceramics
Material switch housing: Stainless steel 304
Material wet portion housing: Stainless steel 316L

Characteristics [2]

With display: Yes
Output signal: 4 - 20 mA
Electrical connection: Plug, M12x1, 4-pin
Level of protection (IP value): IP67
Medium temperature: -40 / 100 °C
Ambient temperature: -25 / 85 °C
Explosion-proof: No

Measuring range	Measuring unit	Size process connection	Supply voltage	Article
0 / 50	mbar	DN40	14.5 - 45V DC	12972826
0 / 50	mbar	DN50	14.5 - 45V DC	12972824
0 / 100	mbar	2" [50]	14.5 - 45V DC	12972828
0 / 100	mbar	DN40	14.5 - 45V DC	12972827
0 / 100	mbar	DN50	14.5 - 45V DC	12972825
0 / 200	mbar	2" [50]	14.5 - 45V DC	12745369
0 / 200	mbar	DN40	14.5 - 45V DC	12745363
0 / 200	mbar	DN50	14.5 - 45V DC	12745366

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.