

ACS S50-K fig. 8350 level sensor



Characteristics

Serie: S50-K
Model: Hydrostatic level transmitter
Measuring method: Pressure
Relative accuracy of measurement: 0.2 % %
Process connection: External thread [BSPP]
Membrane material: Ceramics

Characteristics [2]

Material switch housing: PBT
With display: Yes
Electrical connection: Plug, M12x1, 4-pin
Level of protection (IP value): IP67
Medium temperature: -25 / 100 °C

Measuring range	Measuring unit	Size of process connection	Supply voltage	Article
0 / 2000	mm	3/4" [20]	14.5 - 45V DC	12972819
0 / 1000	mm	3/4" [20]	14.5 - 45V DC	12972818
0 / 1000	mm	3/4" [20]	14.5 - 45V DC	12972821
0 / 2000	mm	3/4" [20]	14.5 - 45V DC	12972822
0 / 4000	mm	3/4" [20]	14.5 - 45V DC	12972823
0 / 500	mm	3/4" [20]	14.5 - 45V DC	12972817
0 / 4000	mm	3/4" [20]	14.5 - 45V DC	12972820

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.