



IGUS Slewing ring iglidur® PRT-01 toothed outer ring made from aluminum sliding elements made from iglidur® J

Characteristics

Series: iglidur®

Type: PRT-01-TO

Rolling element: Sliding element

With sealing: No

Tooththing: External tooththing

Operating temperature: -50 / 90 °C

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Article
PRT-01-20-TO-T10	20	87.25	26	13569279
PRT-01-30-TO-AT10	30	106.4	30.5	13569282
PRT-01-30-TO-HTD8M	30	110.7	30.5	13569283
PRT-01-30-TO-ST	30	112	30.5	13569284
PRT-01-50-TO-T10	50	157.3	33	13569285
PRT-01-60-TO-AT10	60	163.8	34.5	13569286
PRT-01-60-TO-HTD8M	60	166.7	34.5	13569287
PRT-01-60-TO-ST	60	184	34.5	13569288
PRT-01-100-TO-HTD8M	100	187.1	36	13569268
PRT-01-100-TO-AT10	100	189.2	36	13569267
PRT-01-100-TO-T10	100	189.2	36	13569271
PRT-01-100-TO-ST	100	196	36	13569269
PRT-01-150-TO-AT10	150	252.9	36.5	13569272
PRT-01-150-TO-T10	150	252.9	36.5	13569275
PRT-01-150-TO-HTD8M	150	253.3	36.5	13569273
PRT-01-150-TO-ST	150	256	36.5	13569274
PRT-01-200-TO-AT10	200	303.9	41.5	13569276
PRT-01-200-TO-ST	200	308	41.5	13569277
PRT-01-300-TO-AT10	300	456.7	43.5	13569280
PRT-01-300-TO-ST	300	462	43.5	13569281

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.