


WALVOIL Gear flow divider with safety on each section




Characteristics

Type: Type Y, reliefvalve each section

Max. operating pressure: 240 bar

Displacement: 8.5 cm³/r



Volume flow l/min	Connections	Material	Article
8 - 32	IN: 3/4"BSP, OUT: 3/4"BSP	Aluminium	13473568
10 - 30	IN: 3/8"BSP, OUT: 3/8"BSP	Aluminium	13473549
10 - 38	IN: 3/8"BSP, OUT: 3/8"BSP	Aluminium	13473550
12 - 48	IN: 3/4"BSP, OUT: 3/4"BSP	Aluminium	13473569
13 - 47	IN: 3/8"BSP, OUT: 3/8"BSP	Aluminium	13473551
16 - 64	IN: 3/4"BSP, OUT: 1/2"BSP	Aluminium	13473570
22 - 77	IN: 3/4"BSP, OUT: 3/4"BSP	Aluminium	13473571
28 - 84	IN: 3/4"BSP, OUT: 3/4"BSP	Aluminium	13473572
32 - 96	IN: 3/4"BSP, OUT: 3/4"BSP	Aluminium	13473573
44 - 132	IN: 3/4"BSP, OUT: 3/4"BSP	Aluminium	13473574
52 - 156	IN: 3/4"BSP, OUT: 3/4"BSP	Aluminium	13473575

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.