



FESTO Stopper cylinder single acting DFST

Characteristics

Series: DFST

Function: Single acting

Magnetic: Yes

Housing material: Aluminium alloy

Operating temperature: 5 / 60 °C

Manufacturer ID	Cushioning	Bore diameter mm	Stroke length mm	Port Size in	Operating pressure bar	Article
						14167845
DFST-32-20-Y4-A-G2	Shock absorber	32	20	G1/8	2 / 10	14086423
DFST-32-20-Y4-A-S-G2	Shock absorber	32	20	G1/8	2 / 10	14086424
DFST-32-20-L-Y4-A-S-G2	Shock absorber	32	20	G1/8	2 / 10	14086429
DFST-32-20-L-Y4-A-G2	Shock absorber	32	20	G1/8	2 / 10	14086427
DFST-50-30-L-Y4-A-S-G2	Shock absorber	50	30	G1/8	2 / 10	14086402
DFST-50-30-L-Y4-A-G2	Shock absorber	50	30	G1/8	2 / 10	14086401
DFST-63-30-L-Y4-A-G2	Shock absorber	63	30	G1/8	2 / 10	14086409
DFST-63-30-Y4-A-S-G2	Shock absorber	63	30	G1/8	2 / 10	14086406
DFST-63-30-Y4-A-G2	Shock absorber	63	30	G1/8	2 / 10	14086405
DFST-63-30-L-Y4-A-S-G2	Shock absorber	63	30	G1/8	2 / 10	14086410
DFST-80-40-L-Y4-A-S-G2	Shock absorber	80	40	G1/8	2 / 10	14086418
DFST-80-40-Y4-A-S-G2	Shock absorber	80	40	G1/8	2 / 10	14086414
DFST-80-40-L-Y4-A-G2	Shock absorber	80	40	G1/8	2 / 10	14086417
DFST-80-40-Y4-A-G2	Shock absorber	80	40	G1/8	2 / 10	14086413

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.