



ECON® Butterfly valve Type: 4801 Ductile cast iron/Ductile iron with EPDM lining Squeeze handle Groove

Characteristics

Type: 4801

Norm: EN (DIN)

Valve design: Centric

Housing material: Ductile cast iron

Material quality: EN-JL1030

Surface protection: Coated

Connection: Groove

Face to Face norm: Manufacturer standard

Operation: Squeeze handle

Top flange standard: ISO 5211 Direct Mount

Disk material: Ductile iron with EPDM lining

Application

- Recommended in: Utilities

Nominal inner diameter	External tube diameter of connection	Pressure rating	Material liner	Minimum medium temperature [continuous]	Article
	mm			°C	
DN50	60.3	PN10	EPDM	-10	13492671
DN65	76.1	PN10	EPDM	-10	13492672
DN80	88.9	PN10	EPDM	-10	13492673
DN100	114.3	PN10	EPDM	-10	13492674
DN125	139.7	PN10	EPDM	-10	13492675
DN150	168.3	PN10	EPDM	-10	13492676

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.