



FRENZELIT Fibre flange gasket NOVAPRESS 850 EN 1514-1 IBC

Characteristics

Series: NOVAPRESS
Type: 850
Norm: EN 1514-1 IBC
With Inner eyelet: No
Fibre type: Aramid
Anti sticking layer: No
Temperature range: -100 / 130 °C
Max. pressure: 80 bar

Characteristics [2]

Suitable for medium: Chlorine Water < 5%
[7782-50-5], Solvents, Refrigerants, Fuels, Weak
Alkalis, Lubricant, Weak Acids, Biodiesel, Grease,
Food & Beverages, Oil, Natural gas, Potable water,
Chlorine, gaseous [7782-50-5], Air [compressed air]
Approval according to: HTB DIN30653, DVGW W270,
UBA Elastomerleitlinie, TA-Luft, GL, DVGW, WRAS,
EC1935/2004, Blow out VDI2200, FDA

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	2	13531373
DN15	PN10/40	51	22	2	13531374
DN20	PN10/40	61	27	2	13531375
DN25	PN10/40	71	34	2	13531376
DN32	PN10/40	82	43	2	13531377
DN40	PN10/40	92	49	2	13531378
DN50	PN10/40	107	61	2	13531379
DN65	PN10/40	127	77	2	13531380
DN80	PN10/40	142	89	2	13531381
DN100	PN10/16	162	115	2	13531369
DN125	PN10/16	192	141	2	13531370
DN150	PN10/16	218	169	2	13531371
DN200	PN10/16	273	220	2	13531372
DN250	PN10	328	273	2	13531363
DN250	PN16	329	273	2	13531382
DN250	PN25	340	273	2	13684396
DN250	PN40	352	273	2	13684397
DN300	PN10	378	324	2	13531364
DN300	PN16	384	324	2	13531383
DN300	PN25	400	324	2	13684398
DN300	PN40	417	324	2	13684399
DN350	PN10	438	356	2	13531365
DN350	PN16	444	356	2	13531384
DN350	PN25	457	356	2	13684400
DN350	PN40	474	356	2	13684401
DN400	PN10	489	407	2	13531366
DN400	PN16	495	407	2	13531385
DN400	PN25	514	407	2	13684402
DN400	PN40	546	407	2	13684434
DN500	PN10	594	508	2	13531367
DN500	PN16	617	508	2	13531386
DN500	PN25	624	508	2	13684435
DN500	PN40	628	508	2	13684436
DN600	PN10	695	610	2	13531368
DN600	PN16	734	610	2	13531387
DN600	PN25	731	610	2	13684438
DN600	PN40	747	610	2	13684439

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.