


GOODALL Coupling GDF-M-C



Characteristics

- Type of component:** Hose tail coupling
- Material:** AISI 316
- Connection type:** Threaded coupling
- Hose fitting type:** Male thread
- Connection termination:** SMS
- Elbow angle [degr.]:** 0 °
- Hose tail execution:** Serrated, with safety collar
- Temperature range [°C]:** -40 / 205 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
DN15	DN12	40	580	13704443
DN20	DN19	40	580	13704444
DN25	DN25	40	580	13704445
DN32	DN32	40	580	13704446
DN40	DN38	40	580	13704447
DN50	DN50	25	362	13704448
DN65	DN63	25	362	13704449
DN80	DN75	25	362	13704450
DN100	DN100	25	362	13704451
2"	DN50	25	362	14102994
3"	DN75	25	362	14102999
4"	DN100	25	362	14103001

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.