


GOODALL Coupling GDF-F-C



Characteristics

Type of component: Hose tail coupling

Material: AISI316 hose tail/AISI 304 nut rubber covered

Connection type: Threaded coupling

Hose fitting type: Food Female Thread

Characteristics [2]

Connection termination: SMS

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -30 / 260 °C

Connection termination size	Hose ID [DN]	Maximum operating pressure		Article
		bar	psi	
DN15	DN12	40	580	13704434
DN20	DN19	40	580	13704435
DN25	DN25	40	580	13704436
DN32	DN32	40	580	13704437
DN40	DN38	40	580	13704438
DN50	DN50	25	362	13704439
DN65	DN63	25	362	13704440
3" ENG	DN75	25	362	13715400
DN80	DN75	25	362	13704441
DN100	DN100	25	362	13704442
DN25	DN25	40	580	14059316
DN32	DN32	40	580	14059317
DN40	DN38	40	580	14059318
DN50	DN50	25	362	14059319
DN65	DN63	25	362	14059321
DN80	DN75	25	362	14059322

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.