

ECON® V-port ball Stainless steel Suitable for: Premium ball valve Suitable from year of construction: 2017



Characteristics

Material: Stainless steel

Material quality: ASTM A351 CF8M

Application

- Recommended in: Chemical



DN full bore	DN reduced bore	Angle (degrees)	Suitable from year of construction	Article
1.1/2" [40]	2" [50]	30°	2017	13470383
1.1/4" [32]	1.1/2" [40]	30°	2017	13470381
1" [25]	1.1/4" [32]	30°	2017	13470379
1/4" - 3/8" - 1/2"		30°	2017	13470375
2.1/2" [65]	3" [80]	30°	2017	13470387
2" [50]	2.1/2" [65]	30°	2017	13470385
3/4" [20]	1" [25]	30°	2017	13470377
3" [80]	4" [100]	30°	2017	13470420
4" [100]		30°	2017	13470423
1.1/2" [40]	2" [50]	60°	2017	13470384
1.1/4" [32]	1.1/2" [40]	60°	2017	13470382
1" [25]	1.1/4" [32]	60°	2017	13470380
1/4" - 3/8" - 1/2"		60°	2017	13470376
2.1/2" [65]	3" [80]	60°	2017	13470388
2" [50]	2.1/2" [65]	60°	2017	13470386
3/4" [20]	1" [25]	60°	2017	13470378
3" [80]	4" [100]	60°	2017	13470421
4" [100]		60°	2017	13470424
1.1/2" [40]	2" [50]	90°	2017	13470415
1.1/4" [32]	1.1/2" [40]	90°	2017	13470416
1" [25]	1.1/4" [32]	90°	2017	13470413
1/4" - 3/8" - 1/2"		90°	2017	13470414
2.1/2" [65]	3" [80]	90°	2017	13470418
2" [50]	2.1/2" [65]	90°	2017	13470417
3/4" [20]	1" [25]	90°	2017	13470419
3" [80]	4" [100]	90°	2017	13470422
4" [100]		90°	2017	13470425

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.