

ASAHI Pneumatic actuator Series: AR23 Type: 3721 PP Single acting, spring closing

Characteristics

Series: AR23 Type: 3721

Transmission: Quarter turn

Operating principle: Single acting, spring closing

Material housing: PP



Application


 The ASAHI® pneumatic actuators are designed to automate ASAHI ball valves type 23 [3-way ball valve]. The actuators are ideal for the on/off or continuous operation of ASAHI ball valves. Because the actuators are made of high quality plastics the actuators can be perfectly used in a high corrosive environment.

Technical Information

- Spring return normally open or normally closed design.
- Lightweight and compact design.
- Excellent corrosion resistance.
- Easy to mount and unmount of the actuator.
- No bolts needed for mounting because of the "snap-fit" design.
- Air supply compatible with NAMUR standard.
- Suitable for mechanical limit switches or dual proximity sensors.

Construction

• These pneumatic actuators are only suitable for ASAHI Ball valves type 23 (3-way).



Size table:

Α	В	С	н	Weight
mm	mm	mm	mm	kg
154	74	46	107	0.6
194	94	59	134	1
254	110	67	158	2

Model	Nominal inside diameter of valve	Weight	Article
		kg	
AR040NC	1/2" (DN15)	0.6	13610106
AR040NC	3/4" (DN20)	0.6	13610107
AR050NC	1" (DN25)	1	13610108
AR063NC	1.1/4" (DN32)/1.1/2" (DN40)/2" (DN50)	2	13610109

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

PR1579278042976964_EN_18.05.2024

