



Coupling SHWZ

Characteristics

Type of component: Hose tail coupling

Material: AISI 316

Connection type: Welding coupling

Hose fitting type: Weld

Connection termination: Welded end

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 260 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure bar	Maximum operating pressure psi	Article
				12946414
12,7x1,65 [9,4]	DN12	40	580	12946426
17,2x1,6 [14,0]	DN12	40	580	12946416
21,3x1,6 [18,1]	DN12	40	580	12946417
13,0x1,5 [10,0]	DN12	40	580	12959658
26,9x1,6 [23,7]	DN19	40	580	12946418
19,05x1,65 [15,75]	DN19	40	580	12946427
19,0x1,5 [16,0]	DN19	40	580	12959662
23,0x1,5 [20,0]	DN19	40	580	12946408
33,7x2,0 [29,7]	DN25	40	580	12946419
25,4x1,65 [22,1]	DN25	40	580	12946428
42,4x2,0 [38,4]	DN32	40	580	12946420
35,0x1,5 [32,0]	DN32	40	580	12946410
38,1x1,65 [34,8]	DN38	40	580	12946429
48,3x2,0 [44,3]	DN38	40	580	12946421
50,8x1,65 [47,5]	DN50	40	580	12946430
60,3x2,0 [56,3]	DN50	25	362	12946422
70,0x2,0 [66,0]	DN63	25	362	12946413
76,1x2,0 [72,1]	DN63	40	580	12946423
63,5x1,65 [60,2]	DN63	25	362	12946431
70,0x2,0 [66,0]	DN75	25	362	13368706
88,9x2,0 [84,9]	DN75	40	580	12946424
101,6x2,11 [97,38]	DN100	25	362	12946433

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.