



Single filter Type: 1167

Characteristics

Type: 1167

Norm: EN (DIN)/ ASME

Application

- Water, oils, high- and low-density liquids and gases in many applications, materials and pressure ranges
- Can be used in horizontal suction and delivery piping

Technical Information

- PRESSURE CLASS PN 6-PN 160/ASME 150-900
- Flange connections DN 100-DN 1000/4-50inch
- Max. pressure difference according to specification
- Housing material: steel, stainless steel, [Super] Duplex, Hastelloy®, CuNiFe
- Screen material: stainless steel, [Super] Duplex, Hastelloy®, CuNiFe
- Surface treatment: coated, KIWA, galvanised, rubber, PFA- or ECTFE-coated
- Screen design and perforation according to specification
- Vent and drain connections are fitted as standard

Construction

- Welded construction
- Design in accordance with NEN-EN 13445

Options

- Design in accordance with ASME BPVC, Section VIII, Division 1.
- Welding fittings
- Differential pressure measurement and signalling
- Scaled-down connections
- Horizontal and vertical right-angled model
- Position of outlet connection according to specification
- Construction length, height and housing diameter according to specification
- Steam jacket for steam, oil or water
- Version for vertical piping with downwards flow
- Adjustable legs according to specification
- Davit for cover
- Second davit for screen
- Multiple-screen version
- Quick-release or hinged screw for cover
- PED to Cat. IV
- Other designs, dimensions and materials
- Certificate of conformity 3.1, 3.2

Description	Article
Single filter Type: 1167	14084920
Single filter Type: 1167	14084921

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.