


OLEODINAMICA MARCHESINI Double pilot operated check valves VBPDE



Pilot check valves are used to block a cylinder in both directions. The oil flow pass freely in one direction and is blocked in the opposite direction until pilot pressure is applied.

Material:

- Body: zinc-plated steel.
- Internal parts: hardened and ground steel.
- Seals: BUNA N.

Mounting:

- Pipemounting: BSP ports.



Characteristics

Version: Inline mounting

Type of valve: Double

Material: Steel

Steering pressure ratio	Opening pressure	Max. operating pressure bar	Max. oilflow l/min	Connections	Article
1:4	2 bar	300	100	3/4" BSP	14228901
1:4	3,5 bar	350	70	1/2" BSP	14228900
1:5	6 bar	350	50	1/2" BSP	14228898
1:5	8 bar	350	45	3/8" BSP	14228899
1:5,5	3 bar	350	35	3/8" BSP	14228897
1:5,5	4 bar	350	20	1/4" BSP	14228895

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.